

Product information



Product number:	ALT70 - L27
Track System:	2 wire, 4 wire
Input Voltage (v):	48VDC
Dimming:	On/Off, 1-10V, DALI
Light source:	COB LED
luminaire Lifetime:	50.000h (L80-B10, Ta25°C)
Rotation Angle (degree):	350
Tilting Angle (degree):	90
IP Rating:	20
Working Temperature (°C)	-5 ~ +30
Storage Temperature (°C)	-20 ~ +50
Material:	Aluminium
Fitting Colors:	9016 Sandy White / 9017 Sandy Black




Honeycomb L01 Oval diffuser L02 Diffuser L03 Anti-glare ring L04

Packaging information

N.W. lamp (Kg):	0.6
G.W. Carton (Kg):	12
Master carton dimensions(mm):	430x430x390
Quantity per carton:	16

Beam	Watt	CRI	Luminous	CCT	Code
16	27W	90	2615.7 lm	4000K	ALT70S-4LNC27G40-S
			2467.6 lm	3000K	ALT70S-4LNC27G30-S
			2294.9 lm	2700K	ALT70S-4LNC27G27-S
22	27W	90	2621.7 lm	4000K	ALT70S-4LNC27G40-M
			2473.3 lm	3000K	ALT70S-4LNC27G30-M
			2300.1 lm	2700K	ALT70S-4LNC27G27-M
34	27W	90	2458.1 lm	4000K	ALT70S-4LNC27G40-F
			2319.0 lm	3000K	ALT70S-4LNC27G30-F
			2156.7 lm	2700K	ALT70S-4LNC27G27-F
43	27W	90	2449.7 lm	4000K	ALT70S-4LNC27G40-WF
			2311.0 lm	3000K	ALT70S-4LNC27G30-WF
			2149.2 lm	2700K	ALT70S-4LNC27G27-WF



① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

Code composition: ALT 70 S - 4 LN C 27 G30 - S - B - L01

① Product series	② Model	③ App types	④ Track style	⑤ Dimming type	⑥ COB type	⑦ Watt	⑧ LED Kelvin & CRI	⑨ Optical angle	⑩ Finishes	⑪ Accessories
ALT	70	S Spotlight	4 wires	LN No dimming	C COB	27W	H27 2700 >95 S Spot	White	L01 Honeycomb	
				LV 0/1-10V dimming			G30 3000 >90 M Medium	Black	L02 Oval diffuser	
				LD DALI dimming			E40 4000 >80 F Flood		L03 Diffuser	
							C50 5000 >70 WF Wide Flood		L04 Anti-glare ring	