


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm					
NAME:		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:75		Shielding Angle:	

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 83.57 lm/W
MODEL	ALT85-38G30-36	I _{max} (cd)	8139	S/MH(C0/180)	0.55	
NOMINAL POWER(W)	38	LOR(%)	100.0	S/MH(C90/270)	0.55	
RATED VOLTAGE(V)	220-240	TOTAL FLUX(lm)	3167.4	□ UP,DN(C0-180)	0.0,50.4	
NOMINAL FLUX(lm)	3167.39	CIE CLASS	DIRECT	□ UP,DN(C180-360)	0.0,49.6	
LAMPS INSIDE	1	□ up(%)	0.0	CIBSE SHR NOM	0.50	
TEST VOLTAGE(V)	225	□ down(%)	100.0	CIBSE SHR MAX	0.55	

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

□ Range: 0 - 90DEG
□ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


°	C0	C45	C90	C135	C180	C225	C270	C315	°	□ zone	□ total	%lum, lamp
10	6656	6721	6656	6680	6654	6594	6688	6612	0- 10	707.5	707.5	22.3,22.3
20	2873	2969	2879	2907	2885	2790	2890	2834	10- 20	1326	2034	64.2,64.2
30	834.1	867.4	846.1	844.1	795.2	783.8	806.0	798.4	20- 30	729.4	2763	87.2,87.2
40	208.8	219.1	225.6	234.7	225.6	213.6	203.0	199.1	30- 40	274.6	3038	95.9,95.9
50	53.02	53.12	53.17	53.69	51.89	50.88	52.86	51.73	40- 50	88.54	3126	98.7,98.7
60	12.57	12.75	12.02	12.12	12.44	12.39	13.11	12.15	50- 60	25.46	3152	99.5,99.5
70	5.941	6.012	6.241	6.127	6.621	6.146	6.243	5.602	60- 70	8.869	3161	99.8,99.8
80	2.420	2.405	2.348	2.454	2.125	2.229	2.263	2.144	70- 80	4.242	3165	99.9,99.9
90	2.937	2.942	2.943	2.944	1.986	1.968	2.007	1.993	80- 90	2.477	3167	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	6616	6566
80	3158	3061
75	3375	3382
70	3936	4131
65	4696	4998
60	5696	5443
55	10612	10529
50	18689	18726
45	35089	35953


C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:

□cc	80%			70%			50%			30%			10%			0
□w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
□fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio															



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

□ Range: 0 - 90DEG
 □ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm					
NAME:		TYPE:		WEIGHT:	
SPEC.:		DIM.:		SERIAL No.:	
MFR.:		SUR.:75		Shielding Angle:	

<input type="checkbox"/> cc	80%			70%			50%			30%			10%			0														
<input type="checkbox"/> w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
<input type="checkbox"/> fc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients (WEC)														
0.0																														
1.0	.155	.088	.028	.148	.085	.027	.136	.078	.025	.124	.072	.023	.114	.066	.021															
2.0	.146	.080	.025	.140	.077	.024	.130	.072	.022	.120	.067	.021	.111	.063	.020															
3.0	.137	.073	.022	.133	.071	.021	.124	.067	.020	.116	.063	.019	.108	.060	.019															
4.0	.130	.067	.020	.126	.066	.019	.118	.063	.019	.111	.060	.018	.105	.057	.017															
5.0	.123	.063	.018	.119	.061	.018	.113	.059	.017	.107	.056	.017	.101	.054	.016															
6.0	.117	.059	.017	.114	.058	.017	.108	.055	.016	.103	.054	.016	.098	.052	.015															
7.0	.111	.055	.016	.109	.054	.015	.104	.053	.015	.099	.051	.015	.095	.049	.015															
8.0	.106	.052	.015	.104	.051	.014	.100	.050	.014	.096	.048	.014	.092	.047	.014															
9.0	.102	.049	.014	.100	.049	.014	.096	.047	.013	.092	.046	.013	.089	.045	.013															
10.0	.098	.047	.013	.096	.046	.013	.093	.045	.013	.089	.044	.013	.086	.043	.012															

<input type="checkbox"/> cc	80%			70%			50%			30%			10%			0
<input type="checkbox"/> w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
<input type="checkbox"/> fc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Ceiling Cavity Exitance Coefficients(CCEC)												
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.170	.158	.147	.145	.135	.126	.099	.093	.087	.057	.054	.051	.018	.017	.016	
2.0	.153	.133	.116	.131	.114	.100	.090	.079	.070	.052	.046	.041	.017	.015	.013	
3.0	.139	.113	.093	.119	.098	.081	.082	.068	.057	.047	.040	.033	.015	.013	.011	
4.0	.127	.098	.076	.109	.085	.066	.075	.059	.047	.043	.035	.028	.014	.011	.009	
5.0	.118	.086	.063	.101	.075	.055	.070	.052	.039	.040	.031	.023	.013	.010	.008	
6.0	.109	.077	.053	.094	.066	.046	.065	.046	.033	.038	.027	.019	.012	.009	.006	
7.0	.102	.069	.045	.088	.060	.039	.061	.042	.028	.035	.025	.017	.011	.008	.005	
8.0	.096	.062	.039	.083	.054	.034	.057	.038	.024	.033	.022	.014	.011	.007	.005	
9.0	.091	.057	.034	.078	.049	.029	.054	.035	.021	.032	.020	.012	.010	.007	.004	
10.0	.086	.052	.030	.074	.045	.026	.052	.032	.018	.030	.019	.011	.010	.006	.004	

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm										
NAME:			TYPE:			WEIGHT:				
SPEC.:			DIM.:			SERIAL No.:				
MFR.:			SUR.:75			Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	13.8	14.6	14.0	14.7	14.9	13.9	14.7	14.1	14.9	15.0
3H	13.7	14.4	13.9	14.6	14.8	13.8	14.5	14.1	14.7	14.9
4H	13.6	14.3	13.9	14.5	14.7	13.8	14.4	14.0	14.7	14.9
6H	13.6	14.2	13.9	14.4	14.7	13.7	14.3	14.0	14.6	14.8
8H	13.5	14.2	13.8	14.4	14.7	13.7	14.3	14.0	14.5	14.8
12H	13.5	14.1	13.8	14.4	14.6	13.6	14.2	14.0	14.5	14.8
4H 2H	13.6	14.3	13.9	14.5	14.7	13.7	14.4	14.0	14.6	14.8
3H	13.5	14.1	13.8	14.4	14.6	13.6	14.2	13.9	14.5	14.8
4H	13.4	14.0	13.8	14.3	14.6	13.6	14.1	13.9	14.4	14.7
6H	13.4	13.9	13.7	14.2	14.5	13.5	14.0	13.9	14.3	14.7
8H	13.4	13.8	13.7	14.1	14.5	13.5	13.9	13.9	14.3	14.6
12H	13.3	13.8	13.8	14.1	14.5	13.5	13.9	13.9	14.2	14.6
8H 4H	13.3	13.8	13.7	14.1	14.5	13.4	13.9	13.8	14.2	14.6
6H	13.3	13.6	13.7	14.0	14.4	13.4	13.7	13.8	14.1	14.6
8H	13.2	13.6	13.7	14.0	14.4	13.4	13.7	13.8	14.1	14.5
12H	13.3	13.5	13.7	14.0	14.5	13.4	13.7	13.9	14.1	14.6
12H 4H	13.3	13.7	13.7	14.0	14.4	13.4	13.8	13.8	14.2	14.6
6H	13.2	13.5	13.7	13.9	14.4	13.3	13.7	13.8	14.1	14.5
8H	13.2	13.5	13.7	13.9	14.4	13.3	13.6	13.8	14.0	14.5
Variations with the observer position at spacings:										
S = 1.0H	+ 2.6 / - 6.3					+ 2.8 / - 6.5				
1.5H	+ 4.2 / - 5.3					+ 4.5 / - 5.4				
2.0H	+ 5.0 / - 3.9					+ 5.2 / - 4.1				

CIE Pub.117, 3167 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 4.0)

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	79	88	83	79	88	82	79	76
0.80	96	91	87	96	90	87	94	90	87	83
1.00	100	95	92	100	95	91	98	94	91	87
1.25	104	99	96	103	99	96	101	98	95	91
1.50	107	102	99	106	102	99	103	100	98	93
2.00	109	105	102	108	104	101	105	102	100	95
2.50	111	107	104	109	106	103	106	104	101	96
3.00	112	109	106	110	108	105	107	105	103	97
4.00	114	111	109	112	110	108	109	107	105	98
5.00	115	113	111	113	111	110	109	108	107	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: AE
Test Date: 2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 7.240m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

AAI Figure

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 15.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:AE
 Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

LED Avg.L Report

Test:U:225.0V I:0.1750A P:37.90W PF:0.9600 Freq:50.00Hz Lamp Flux:3167.39x1 lm		
NAME:	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:75	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	4917
L_0~180 (75) av	3429
L_0~180 (85) av	5799
L_90~270 (65) av	4958
L_90~270 (75) av	3469
L_90~270 (85) av	5794
L_45 (65) av	4617
L_45 (75) av	3430
L_45 (85) av	5859

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:AE
Test Date:2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 15.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: AE
Test Date: 2020-03-06

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity: 65.0%
Test Distance: 7.240m [K=1.0000]
Remarks:

☐ Range: 0 - 90DEG
☐ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
 Humidity:65.0%
 Test Distance:7.240m [K=1.0000]
 Remarks:

```

Range: 0 - 90DEG
Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.362
Humidity:65.0%
Test Distance:7.240m [K=1.0000]
Remarks:

```