


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm					
NAME: M20-T41004B-24G40-L24			TYPE:		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:436*21.6		Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA				Eff: 76.60 lm/W
MODEL	4000K CRI90	I _{max} (cd)	6955	S/MH(C0/180)	0.43	
NOMINAL POWER(W)	24	LOR(%)	100.0	S/MH(C90/270)	0.48	
RATED VOLTAGE(V)	226	TOTAL FLUX(lm)	1839.8	η UP,DN(C0-180)	0.0,48.9	
NOMINAL FLUX(lm)	1839.84	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,51.1	
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	0.50	
TEST VOLTAGE(V)	225.1	η down(%)	100.0	CIBSE SHR MAX	0.50	



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	5176	5037	4790	4524	4497	4619	4943	5256	0- 10	556.1	556.1	30.2,30.2
20	1759	1678	1584	1455	1447	1498	1716	1925	10- 20	836.8	1393	75.7,75.7
30	244.9	241.3	231.2	209.8	231.9	235.3	278.7	326.3	20- 30	343.0	1736	94.4,94.4
40	24.00	23.48	23.17	25.12	48.55	49.29	50.30	51.92	30- 40	62.85	1799	97.8,97.8
50	5.347	4.261	4.246	4.512	21.21	21.06	21.63	22.07	40- 50	17.27	1816	98.7,98.7
60	1.709	1.707	1.755	1.775	11.79	11.89	12.19	12.45	50- 60	7.857	1824	99.1,99.1
70	2.259	2.260	2.285	2.317	8.459	8.537	8.735	8.892	60- 70	6.100	1830	99.5,99.5
80	2.627	2.617	2.618	2.636	6.175	6.236	6.372	6.459	70- 80	5.248	1835	99.8,99.8
90	2.892	2.848	2.857	2.885	4.664	4.651	4.745	4.841	80- 90	4.498	1840	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1809.2 lm

%lum = 98.3%

%lamp = 98.3%

Conical surface Flux(120deg): 1824 lm

%lum = 99.1%


%lamp = 99.1%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ZR
 Test Date:2021-08-18

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
 Humidity:65.0%
 Test Distance:8.402m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm		
NAME: M20-T41004B-24G40-L24	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:436*21.6	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm		
NAME: M20-T41004B-24G40-L24	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:436*21.6	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.12	1.10	1.09	1.10	1.09	1.07	1.06	1.05	1.04	1.03	1.02	1.01	.99	.98	.98	.96
2.0	1.07	1.04	1.01	1.05	1.02	.00	1.02	.00	.98	.99	.97	.96	.96	.95	.94	.92
3.0	1.02	.98	.95	1.01	.97	.94	.98	.95	.93	.96	.94	.92	.94	.92	.90	.89
4.0	.98	.94	.90	.97	.93	.90	.95	.91	.89	.93	.90	.88	.91	.89	.87	.86
5.0	.94	.90	.86	.93	.89	.86	.91	.88	.85	.90	.87	.85	.88	.86	.84	.83
6.0	.90	.86	.83	.90	.86	.83	.88	.85	.82	.87	.84	.82	.86	.83	.81	.80
7.0	.87	.83	.80	.87	.82	.80	.85	.82	.79	.84	.81	.79	.83	.81	.78	.77
8.0	.84	.80	.77	.84	.80	.77	.83	.79	.77	.82	.79	.76	.81	.78	.76	.75
9.0	.82	.77	.74	.81	.77	.74	.80	.77	.74	.80	.76	.74	.79	.76	.74	.73
10.0	.79	.75	.72	.79	.75	.72	.78	.74	.72	.77	.74	.72	.77	.74	.71	.71



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ZR
 Test Date:2021-08-18

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
 Humidity:65.0%
 Test Distance:8.402m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm					
NAME: M20-T41004B-24G40-L24			TYPE:		WEIGHT:
SPEC.:			DIM.:		SERIAL No.:
MFR.:			SUR.:436*21.6		Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.146	.083	.026	.139	.079	.025	.126	.073	.023	.115	.066	.021	.104	.061	.020	
2.0	.134	.074	.023	.129	.071	.022	.119	.066	.020	.109	.061	.019	.100	.057	.018	
3.0	.125	.067	.020	.120	.064	.019	.112	.061	.018	.104	.057	.017	.097	.053	.017	
4.0	.117	.061	.018	.113	.059	.018	.106	.056	.017	.099	.053	.016	.093	.051	.015	
5.0	.110	.056	.016	.107	.055	.016	.101	.052	.015	.095	.050	.015	.090	.048	.014	
6.0	.104	.052	.015	.102	.051	.015	.096	.049	.014	.091	.047	.014	.087	.046	.014	
7.0	.099	.049	.014	.097	.048	.014	.092	.047	.013	.088	.045	.013	.084	.043	.013	
8.0	.095	.046	.013	.092	.046	.013	.088	.044	.013	.084	.043	.012	.081	.042	.012	
9.0	.090	.044	.012	.089	.043	.012	.085	.042	.012	.082	.041	.012	.078	.040	.011	
10.0	.087	.042	.012	.085	.041	.011	.082	.040	.011	.079	.039	.011	.076	.038	.011	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.169	.158	.147	.145	.135	.127	.099	.093	.088	.057	.054	.051	.018	.017	.016	
2.0	.151	.133	.117	.130	.114	.101	.089	.079	.071	.051	.046	.041	.016	.015	.013	
3.0	.137	.113	.095	.117	.098	.082	.080	.068	.058	.046	.040	.034	.015	.013	.011	
4.0	.124	.098	.078	.107	.085	.068	.073	.059	.048	.042	.035	.028	.014	.011	.009	
5.0	.114	.086	.065	.098	.074	.057	.067	.052	.040	.039	.030	.024	.013	.010	.008	
6.0	.105	.076	.055	.090	.066	.048	.062	.046	.034	.036	.027	.020	.012	.009	.007	
7.0	.098	.068	.047	.084	.059	.041	.058	.041	.029	.034	.024	.017	.011	.008	.006	
8.0	.091	.061	.040	.079	.053	.035	.054	.037	.025	.032	.022	.015	.010	.007	.005	
9.0	.086	.056	.035	.074	.048	.031	.051	.034	.022	.030	.020	.013	.010	.007	.004	
10.0	.081	.051	.031	.070	.044	.027	.048	.031	.019	.028	.018	.011	.009	.006	.004	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm											
NAME: M20-T41004B-24G40-L24					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.:					SUR.: 436*21.6			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	2.5	3.2	2.7	3.4	3.5	2.7	3.4	2.9	3.5	3.7	
	3H	2.6	3.2	2.8	3.4	3.6	2.7	3.4	3.0	3.6	3.8
	4H	2.8	3.4	3.0	3.6	3.8	2.9	3.5	3.2	3.8	4.0
	6H	3.3	3.9	3.6	4.1	4.3	3.4	4.0	3.7	4.2	4.4
	8H	3.7	4.3	4.0	4.5	4.8	3.8	4.3	4.1	4.6	4.8
12H	4.4	4.9	4.7	5.2	5.4	4.4	4.9	4.7	5.2	5.5	
4H	2H	2.3	3.0	2.6	3.2	3.4	2.5	3.1	2.8	3.3	3.6
	3H	2.5	3.0	2.8	3.3	3.6	2.7	3.2	3.0	3.5	3.7
	4H	2.9	3.4	3.2	3.7	4.0	3.0	3.5	3.4	3.8	4.1
	6H	3.7	4.1	4.1	4.5	4.8	3.8	4.2	4.2	4.5	4.9
	8H	4.4	4.8	4.8	5.1	5.5	4.4	4.8	4.8	5.2	5.5
12H	5.3	5.7	5.7	6.0	6.4	5.3	5.7	5.7	6.0	6.4	
8H	4H	3.0	3.5	3.4	3.8	4.2	3.2	3.6	3.5	3.9	4.3
	6H	4.2	4.5	4.6	4.9	5.3	4.2	4.6	4.7	5.0	5.4
	8H	5.1	5.4	5.5	5.8	6.2	5.1	5.4	5.5	5.8	6.3
	12H	6.3	6.6	6.8	7.0	7.5	6.3	6.6	6.8	7.0	7.5
	12H	4H	3.1	3.5	3.5	3.8	4.2	3.2	3.6	3.6	4.0
6H	4.3	4.6	4.8	5.1	5.5	4.4	4.7	4.8	5.1	5.6	
8H	5.4	5.6	5.8	6.1	6.5	5.4	5.7	5.9	6.1	6.6	
Variations with the observer position at spacings:											
S = 1.0H	+ 1.1 / - 0.7					+ 1.0 / - 0.8					
1.5H	+ 2.3 / - 0.7					+ 2.1 / - 0.7					
2.0H	+ 0.5 / - 0.3					+ 0.4 / - 0.3					

CIE Pub.117, 1840 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 2.1$)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm		
NAME: M20-T41004B-24G40-L24	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:436*21.6	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	90	84	81	90	84	81	89	84	81	77
0.80	97	92	88	97	92	88	95	91	88	85
1.00	101	96	93	100	95	92	99	95	92	88
1.25	105	100	97	104	99	96	102	98	95	92
1.50	107	103	100	106	102	99	104	101	98	94
2.00	109	105	103	108	104	102	105	102	100	95
2.50	111	107	105	109	106	104	106	104	102	96
3.00	112	109	107	111	108	105	107	105	103	97
4.00	114	112	110	112	110	108	109	107	106	99
5.00	115	113	112	113	112	110	109	108	107	100
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm		
NAME: M20-T41004B-24G40-L24	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:436*21.6	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

AAI Figure

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm		
NAME: M20-T41004B-24G40-L24	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:436*21.6	Shielding Angle:




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm		
NAME: M20-T41004B-24G40-L24	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:436*21.6	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:ZR
Test Date:2021-08-18

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:48.00V I:0.5004A P:24.02W PF:1.000 Freq:50.00Hz Lamp Flux:1839.84x1 lm		
NAME: M20-T41004B-24G40-L24	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.:	SUR.:436*21.6	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	1504
L_0~180 (75) av	1984
L_0~180 (85) av	4899
L_90~270 (65) av	1547
L_90~270 (75) av	2036
L_90~270 (85) av	5022
L_45 (65) av	1548
L_45 (75) av	2033
L_45 (85) av	5013

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:ZR
 Test Date:2021-08-18

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
 Humidity:65.0%
 Test Distance:8.402m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: ZR
Test Date: 2021-08-18

γ Range: 0 - 90DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity: 65.0%
Test Distance: 8.402m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.354
Humidity:65.0%
Test Distance:8.402m [K=1.0000]
Remarks:

```