

EDGE II

Recessed Downlight

Product information



Product number:	REG2075A - 11W
Input Voltage (v):	220-240V
Dimming:	On/Off, TRIAC, 1-10V, DALI
Light source:	COB LED
luminaire Lifetime:	50.000h (L80-B10, Ta25°C)
Rotation Angle (degree):	350
Tilting Angle (degree):	30
IP Rating:	20
Working Temperature (°C)	-5 ~ +30
Storage Temperature (°C)	-20 ~ +50
Material:	Aluminium
Fitting Colors:	9016 Sandy White / 9017 Sandy Black






Square Trim




Square Trimless

Packaging information

N.W. lamp (Kg)	0.37
G.W. Carton (Kg)	18
Master carton dimensions(mm)	678x670x277
Quantity per carton(PCS)	40

Beam	Watt	CRI	Luminous	CCT	Code
20 	11W	90	819.2	4000K	REG2075AS-11G40
			726.7	3000K	REG2075AS-11G30
			675.8	2700K	REG2075AS-11G27
31 	11W	90	824.2	4000K	REG2075AM-11G40
			730.6	3000K	REG2075AM-11G30
			679.5	2700K	REG2075AM-11G27
40 	11W	90	871.8	4000K	REG2075AF-11G40
			772.7	3000K	REG2075AF-11G30
			718.6	2700K	REG2075AF-11G27



Code composition: REG2 075 A R1 W - R S 01 - D 20 G27

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩ ⑪

Product Code	Hole Cut Size	Structural	Structural style	Finishes	Optical	Angle	Anti-glare cover	Dimming	Watt	LED	Kelvin & CRI	
REG2	Φ95mm	Fixed	R1 Round Trim	White	Reflector	S Spot	01 Mirror silver	X Not-Driver	20W	H27	2700 95	
	Φ75mm	Adjustable	R2 Round Trimless	Black	Lens	M Medium	02 Flax Silver	T TRIAC		G27	2700 90	
	Φ55mm	Wall Washer	S1	Square Trim			F Flood	03 Matte white	V 1-10V		G30	3000 90
				S2 Square Trimless				04 Blinding black	D DALI		G40	4000 90
							05 Bright black		E50	5000 80		
							06 Matte black					
							07 Charm Gold					